



Nitrile

The world's leading disposable glove for chemical splash protection*

- Proprietary Ansell material formulation offers enhanced chemical splash protection
- Soft nitrile blend provides high levels of comfort
- Robust design for superior durability
- Highly versatile for use across a broad range of industries and applications
- Silicone free for product protection

Industries

- Automotive and transportation
- Chemical and petrochemical
- Food processing
- General industry
- Life sciences
- Machinery and equipment

Applications

- Chemical handling
- Cleaning equipment
- Industrial production
- Laboratory analysis
- Maintenance
- Meat, fish and food processing
- Sample taking and processing
- Transferring liquids and solids



TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

Product	92-600	92-605
Material	Nitrile	
Color	Green	
Glove Design	Ambidextrous, Powder Free, Smooth Grip	Ambidextrous, Powder Free, Textured Fingers
Cuff	Beaded Cuff	
Manufacturing/QMS Audit Standards	ISO 9001	
Regulatory/Standards Compliance	EN420, EN374/1,2,3, ASTM D6319, FDA 21 CFR 177-2600, Compliant with U.S. Food Contact Regulations, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities.	
Packaging	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons	
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country of Origin	Sri Lanka / Thailand	Thailand
User Needs Segment	Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times.	High Risk Glove - Extended cuff gloves that provide additional protection for the wrist and the forearm.

PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES				TESTING METHOD
SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10	ASTM D3767/EN 420
Length (mm/in)	92-600	240/9.5	240/9.5	240/9.5	
	92-605	300/11.8	300/11.8	300/11.8	
Average Palm Width (mm/in)	92-600	85/3.35	96/3.74	105/4.13	
	92-605	82/3.23	90/3.54	99/3.90	105/4.13

Freedom from Holes (Inspection level I)	92-600	4.0 AQL (Americas) / 1.5 AQL (Outside of Americas)	ASTM D5151/EN 374-2
	92-605	All regions 1.5 AQL	
Palm Thickness Single Wall	mm: 0.12 / mils: 4.7		ASTM D3767/EN 420

	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength	> 14 Mpa	> 14 Mpa	ASTM D 412-06a
Elongation at Break (%)	> 500	> 400	ASTM D 412-06a
Force at break (N)	> 6	> 6	EN 455-2

ORDERING INFORMATION:

	SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
92-600	ASPN US	552822	552823	552824	552825
	ORACLE US	105077	105018	105079	105080
	ASPN OTHERS	552942	552943	552944	552945
92-600 VEN	CANADA MPRN	9260000S-VEN	9260000M-VEN	9260000L-VEN	9260000XL-VEN
92-605	ASPN	588104	588105	588106	588107

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 2 528 74 00
F: +32 2 528 74 01

Asia Pacific
Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 8310 6688
F: +60 3 8318 6699

North America
Ansell Healthcare Products LLC
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Regulatory Compliance

EAC **CE** 0493
TP TC 019/2011

Performance Standards

92-600



92-605

