Material Safety Data Sheet



Revision Number: 007.0



1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product use:

Company address: Henkel Canada Corporation

2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3

LOCTITE 567 THREAD SEALANT known as LOCTITE® 567™ PST® PIPE SEALAN Sealant IDH number:

135491

Item number:56747Region:CanadaContact information:Telephone:905.814.6511MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC

Internet: www.henkelna.com

1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

		EMERGENCY OVERVIEW	
Physical state: Color: Odor:	Paste White Mild	WHMIS hazard class:	D.2.A, D.2.B
WARNING	6:	CAUSES EYE IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CAUSE SKIN IRRITATION.	
Relevant routes of exposure:		Skin, Inhalation, Eyes, Inhalation	
Potential Health Effec Inhalation Skin cont Eye conta Ingestion	n: act: act:	May cause respiratory tract irritation. May cause skin irritation. May cause allergic skin reaction. Contact with eyes will cause irritation. May cause gastrointestinal tract irritation if swallowed.	

Existing conditions aggravated by Eye, skin, and respiratory disorders. **exposure:**

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Bisphenol A fumarate resin	39382-25-7	30 - 60	
Polyglycol dimethacrylate	25852-47-5	10 - 30	
Polyglycol laurate	9004-81-3	10 - 30	
Polyethylene glycol monococoate	61791-29-5	10 - 30	
Ethene, tetrafluoro-, homopolymer	9002-84-0	5 - 10	
Titanium dioxide	13463-67-7	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
Saccharin	81-07-2	1 - 5	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	1 - 5	
Ethylene glycol	107-21-1	0.1 - 1	
Cumene	98-82-8	0.1 - 1	

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medic attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Flash point:	> 93.3 °C (> 199.94 °F)
Autoignition temperature:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Toxic fluorine compounds. Irritating organic vapours.
Sensitivity to Mechanical Impact:	Not available.
Sensitivity to static discharge:	Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

IDH number: 135491

Storage:

For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Bisphenol A fumarate resin	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Polyglycol laurate	None	None	None	None
Polyethylene glycol monococoate	None	None	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Saccharin	None	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None

Engineering controls:

Respiratory protection:

Eye/face protection:

Skin protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists. If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator must be used.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Neoprene, Butyl-rubber, or nitrile-rubber gloves. Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Paste

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Boiling point/range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

White Mild Not available. Not applicable $< 5 \text{ mm} \text{ hg} (27 \text{ }^{\circ}\text{C} (80.6 \text{ }^{\circ}\text{F}))$ Not available. Not available. $> 93.3 \text{ }^{\circ}\text{C} (> 199.94 \text{ }^{\circ}\text{F})$ Not available. Not available. Not available.

Product name: LOCTITE 567 THREAD SEALANT known as LOCTITE® 567™ PST® PIPE SEALAN Page 3 of 6 Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Not available. Not available. Slight Not available. 0.13 %; 1.38 g/l Method 40 CFR Part 63 Appendix A to Subpart PPPP

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.	
Hazardous decomposition products:	Oxides of nitrogen. Oxides of carbon. Oxides of sulfur. Toxic fluorine compounds. Phenolics. Irritating organic vapours.	
Incompatible materials:	Free radical initiators. Amines. Aldehydes. Alkalis. copper Aluminum. Rust. Bases. Acids. Strong oxidizing agents. Peroxides. Iron. Reducing agents. Zinc.	
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. Exposure to sunlight.	
11. TOXICOLOGICAL INFORMATION		
Acute oral product toxicity:	LD50 (rat) > 10,000 mg/kg	

Acute oral product toxicity: Acute dermal product toxicity:

LD50 (rabbit) > 2,000 mg/kg

Toxicologically synergistic products:

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Not available.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Bisphenol A fumarate resin	No	No	No	No
Polyglycol dimethacrylate	No	No	No	No
Polyglycol laurate	No	No	No	No
Polyethylene glycol monococoate	No	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No	No
Titanium dioxide	No	Group 2B	No	Group A4
Silica, amorphous, fumed, crystal-free	No	No	No	No
Saccharin	No	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No	No
Ethylene glycol	No	No	No	Group A4
Cumene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No	No

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Bisphenol A fumarate resin	None	No Target Organs
Polyglycol dimethacrylate	None	Allergen, Irritant
Polyglycol laurate	None	Allergen, Irritant
Polyethylene glycol monococoate	None	No Target Organs
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Saccharin	None	No Target Organs
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Ethylene glycol	Oral LD50 (RAT) = 5.89 g/kg Dermal LD50 (RABBIT) = 9,530 mg/kg	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic
Cumene	Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Central nervous system, Irritant, Lung

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:

Not regulated None None None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2,4,5,6,7,8,10

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.