



Revision Number: 003.0 Issue date: 04/28/2015

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: LOCTITE 592 MEDIUM STRENGTH

THREAD SEALANT known as

LOCTITE® 592™ PST® PIPE SEALAN

Product use: Sealant

2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3

Item number:59241Region:Canada

Company address:Contact information:Henkel Canada CorporationTelephone: 905.814.6511

MEDICAL EMERGENCY Phone: Poison Control Center

88568

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste WHMIS hazard class: D.2.A, D.2.B

Color: White Odor: Mild

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: May cause respiratory tract irritation. Vapors may cause headaches, nausea, dizziness and

respiratory tract irritation.

Skin contact: May cause allergic skin reaction. May cause skin irritation with discomfort or rash.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May be harmful if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Bisphenol A fumarate resin	39382-25-7	10 - 30	
Mica	12001-26-2	10 - 30	
Polyglycol dimethacrylate	25852-47-5	10 - 30	
Polyglycol dioctanoate	18268-70-7	10 - 30	
Octan-1-ol	111-87-5	10 - 30	
Ethene, tetrafluoro-, homopolymer	9002-84-0	5 - 10	
Silica, amorphous, treated	68909-20-6	1 - 5	
Titanium dioxide	13463-67-7	1 - 5	
Propane-1,2-diol	57-55-6	1 - 5	
Cumene	98-82-8	0.1 - 1	

IDH number: 88568 Product name: LOCTITE 592 MEDIUM STRENGTH THREAD SEALANT known as LOCTITE® 592™
PST® PIPE SEALAN

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Toxic fluorine compounds. Irritating organic vapours.

Sensitivity to Mechanical Impact: Not available.

Sensitivity to static discharge: Not available.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Canada Customer Service at 800-263-5043.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Bisphenol A fumarate resin	None	None	None	None
Mica	3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA	None	None
Polyglycol dimethacrylate	None	None	None	None
Polyglycol dioctanoate	None	None	None	None
Octan-1-ol	None	None	50 ppm (265 mg/m3) TWA	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Silica, amorphous, treated	10 mg/m3 TWA Inhalable dust.	6 mg/m3 TWA	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:
Color:
White
Odor:
Mild
Odor threshold:
pH:
Not available.
Not applicable

 Vapor pressure:
 < 10 mm hg (27 °C (80.6 °F))</td>

 Boiling point/range:
 > 149 °C (> 300.2 °F)

Melting point/ range:Not available.Specific gravity:1.21Vapor density:Not available.

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Not available.
Not available.
Slight

IDH number: 88568 Product name: LOCTITE 592 MEDIUM STRENGTH THREAD SEALANT known as LOCTITE® 592™

Partition coefficient (n-octanol/water): Not available. VOC content: 0.72 %; 6.86 g/l

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated

temperature or in the presence of incompatible materials.

Hazardous decomposition products: Oxides of carbon. Toxic fluorine compounds. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition.

Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg

Acute dermal product toxicity: LD50 (rabbit) > 5,000 mg/kg

Toxicologically synergistic products: Not available.

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Bisphenol A fumarate resin	No	No	No	No
Mica	No	No	No	No
Polyglycol dimethacrylate	No	No	No	No
Polyglycol dioctanoate	No	No	No	No
Octan-1-ol	No	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No	No
Silica, amorphous, treated	No	No	No	No
Titanium dioxide	No	Group 2B	No	Group A4
Propane-1,2-diol	No	No	No	No
Cumene	No	Group 2B	No	No

Hazardous components	LD50s and LC50s	Health Effects/Target Organs	
Bisphenol A fumarate resin	None	No Target Organs	
Mica	None	Lung	
Polyglycol dimethacrylate	None	Allergen, Irritant	
Polyglycol dioctanoate	None	Irritant	
Octan-1-ol	Oral LD50 (RAT) = > 5 g/kg Dermal LD50 (RABBIT) = > 5 g/kg	Central nervous system, Irritant	
Ethene, tetrafluoro-, homopolymer	None	No Target Organs	
Silica, amorphous, treated	None	No Target Organs	
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity	
Propane-1,2-diol	Oral LD50 (RABBIT) = 18 g/kg Oral LD50 (RAT) = 30 g/kg	Irritant	
Cumene	Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Central nervous system, Irritant, Lung	

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 88568 Product name: LOCTITE 592 MEDIUM STRENGTH THREAD SEALANT known as LOCTITE® 592™

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None

Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

IDH number: 88568

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2,4,5,6,7,8,10

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.